



## AL200W

200W single output UPS switching power supply

### Specification

DC output voltage	C H 1: 13.8 V	C H 2:13.8V(charge battery)
Output voltage error (Note: 2)	±1%	-----
Rated output current	5A	18A
Output current rage	0-5A	-----
Wave and noise(Note : 3)	120mVp-p	-----
DC output power	70W	
Efficiency	84%	84 %
Adjustable range for DC voltage	C H 1:1 1.3~14.2 V	C H 2:10~1 3.8 V
AC input voltage range	88-132VAC/170-264V AC Selected by switch,47-63Hz: 240-370VDC	
Input current	3.5A/115VAC 2A/230VAC	
AC Inrush current	50A/115VAC 50A/230VAC	
Leakage current	<1mA/240VAC	
Overload protection	105%-150%Type:Foldback:current limiting reset: auto recovery	
Battery low voltage protection	9.5~11V	
UPS function	High efficiency charge, Battery can be charged more than 90% full	
	Cut charging automatically when finish charge, protect battery from overcharge	
	Utility Power and battery switch automatically	
	Cold start function, battery can start UPS when utility power cut	

Temperature coefficient	±0.03%/°C (0-50°C)
Setup rise hold up time	200ms,50ms,20ms
Vibration	10-500Hz,2G 10min,/1cycle, Period for60min, Each axes
Withstand voltage	Input and output internal: 1.5KVAC,Input and enclosure: 1.5KVAC,Output and enclosure: 0.5KVAC
Isolation resistance	Input and output internal: Input and enclosure, Output and enclosure: 500VDC/100MΩ
Working temperature and humidity	-10°C~+60°C (Refer to output derating curve) , 20%~90%RH
Store temperature and humidity	-20°C~+85°C。 10%~95%RH
Overall dimension	215*115*50
Weight	0.7Kgs

Note:

- 1.The testing condition for the parameter above is :230VAC input, rated load,25°C70% RH.Humidity.
2. Error.include the setting error, line stability and load stability. (Note: 5).
- 3.Wave test: adopting "A12"double wire for 20MHz, and 0.1UF&47UF capacitor short-circuit for interrupting.
4. Inlet voltage stability test: when is over load, the lowest voltage of inlet is up to the highest voltage.
5. Load stability test: the load is from 0% to 100%.

**Hiltron Land S.r.l.**

Strada Provinciale di Caserta, 218 80144 - Napoli - Italy  
Tel: (+39) 081.185.39.000 Fax: (+39) 081.185.39.016  
[www.hiltronsecurity.net](http://www.hiltronsecurity.net)